

## NOTES:

M19 STAINLESS STEEL HEX HEAD BOLT, LOCK WASHERS AND NUTS

HEX HEAD BOLT, LOCK WASHER (DRILL AND TAP POLE TO ACCEPT)

UNLESS OTHERWISE NOTED

PIN AND COTTER KEY

PLAN "SIGNAL HEAD MOUNTING DETAILS MAST ARM AND SPAN WIRE MOUNTINGS" .

PLAN "SIGNAL HEAD MOUNTING DETAILS

MAST ARM AND SPAN WIRE MOUNTINGS" .

PLAN "SIGNAL HEAD MOUNTING DETAILS MAST ARM AND SPAN WIRE MOUNTINGS" .

HEAD BOLT AND LOCK WASHERS (DRILL

AND TAP POLE TO ACCEPT

OF NIPPLE

TO ACCEPT)

BACKPLATES SHALL BE INSTALLED WITH 6 STAINLESS STEEL SCREWS AND WASHERS.

ALL DIMENSIONS ARE IN MILLIMETERS UNLESS OTHERWISE NOTED

> **MISCELLANEOUS** SIGNAL DETAILS

## STANDARD PLAN J-6h

APPROVED FOR PUBLICATION STATE DESIGN ENGINEER WASHINGTON STATE DEPARTMENT OF TRANSPORTATION OLYMPIA, WASHINGTON